

# EU SYN 400E-30

- Switching time  $\leq 100\text{ms}$
- Supporting self-feeding and self-restoring
- Modular design, easy to install and maintain
- Automatically switch to the intermediate state when the power supply is missing



**GROWATT**

[www.ginverter.com](http://www.ginverter.com)

P O W E R  
- I N G O  
T O M O -  
R R O W O

**Input Data(AC/Grid)**

Max. AC apparent power	220kVA
Nominal AC voltage	380/400/415V
AC grid frequency	50Hz/60Hz
Max. input current	400A
AC grid connection type	3P4W+PE

**Input Data(GEN)**

Max. AC apparent power	220kVA
Nominal AC voltage	380/400/415V
AC grid frequency	50Hz/60Hz
Max. input current	320A
AC grid connection type	3P4W+PE

**Output Data(Load)**

AC nominal power	200kW
Max. AC apparent power	220kVA
Nominal AC voltage/range	380/400/415V
Max. output current	400A
Max. continuous current	320A

**General Data**

Dimensions (W / H / D)	660/770/288mm
Weight	45kg
Operating temperature range	-25°C ~ 60°C (>50°C derating)
Altitude	4000m
Cooling	Nature convection
Protection degree	IP66/NEMA 4X
Installation	Wall Mountable

IEC 62109